

# PLASTER PLUS

## THIN FILM CEMENT RENDER COATING SYSTEM

### 2 Pack Mineral Based



<b>DESCRIPTION</b>	Similar to a sponge finished (scrub fine) render in appearance, <b>PLASTER PLUS</b> is a 2 pack polymer modified mineral blended plaster. Because of its adhesion, PLASTER PLUS is free-hand applied over Quickwall keyed SKIMCOAT to a smooth undulating sanded finish and top coated with Quickwall Aquaseal Membrane paint– refer to Aquaseal Specification Sheet for equivalent.
<b>SUITABLE FOR</b>	<ul style="list-style-type: none"> <li>• Bricks</li> <li>• Prepared Concrete</li> <li>• Single Skin Masonry Blocks</li> <li>• Quick Clad</li> <li>• Quick Panel</li> <li>• Hebel Products</li> </ul>
<b>SPECIAL FEATURES</b>	<ul style="list-style-type: none"> <li>• Faster than solid plaster to apply, covering more surface area daily for the same number of applicators.</li> <li>• Incorporated waterproofing additives.</li> <li>• Excellent for packing thick sections in one application, maintains internal moisture for thin set plaster while curing, even suction providing extended control of finishing techniques.</li> <li>• Highly modified cement. Environment friendly, wash up in water.</li> </ul>
<b>Even Substrates</b>	Splash coat the substrate with Quickwall SKIMCOAT prior to the <b>PLASTER PLUS</b> application.
<b>Uneven Substrates</b>	Apply 3 mm minimum thickness of Quickwall SKIMCOAT to the substrate, leaving a keyed rough flat base coat, prior to PLASTER PLUS.
<b>Non-Flexible</b>	<b>PLASTER PLUS</b> is the least flexible coating with similar behaviour to solid plaster.
<b>PAINTING</b>	The substrate can be painted after 48 hours under normal conditions. Paint with Quickwall Aquaseal Membrane paint– refer to Aquaseal Specification Sheet for equivalent.
<b>NOTE</b>	<b>PLASTER PLUS</b> can be applied by plaster / mortar machines without blockages commonly experienced with standard cement plaster.
<b>APPROVED FOR</b>	Government Projects, Defence Housing Authority, Commercial and Domestic applications.
<b>GUARANTEE</b>	Ten years when applied by an Approved Applicator and in accordance to Quickwall specification.
<b>SPECIFICATION</b>	<p>1<sup>st</sup> Coat: Apply Quickwall SKIMCOAT</p> <p>2<sup>nd</sup> Coat: Apply Quickwall <b>PLASTER PLUS</b></p> <p>3<sup>rd</sup> Coat: Apply 1 Coat of AQUASEAL membrane paint</p> <p>4<sup>th</sup> Coat: Apply 1 coat of AQUASEAL membrane paint</p>