

# QUICKCRETE

## SPRAYABLE FLUID TILES OR SEAMLESS FLOORS

### 2 Pack Mineral Based



<b>DESCRIPTION</b>	<p><b>QUICKCRETE</b> is a 2 pack polymer ceramic cementitious material for seamless or patterned floors. It can be coloured using natural oxides on site.</p> <p>Patterns are generally created by adhering to the floor cross woven filament tape in the desired format, logo, decal etc. <b>QUICKCRETE</b> is then spray-applied by gravity feed hand held hopper gun or in the case of exceptionally large surface areas applied by rotor screw machines.</p> <p><b>QUICKCRETE</b> will give minor colour variations to the floor's finish and therefore it is recommended that the complete surface area be coated in a continuous manner.</p> <p>Secondary colour spotting with another hopper gun provides an attractive finish but is used very sparingly.</p> <p><b>QUICKCRETE</b> is tough, is finely textured and withstands heavy traffic.</p>
<b>SUITABLE FOR</b>	Patios, driveways, pool surrounds, commercial areas, retail and shopping centres; new concrete or dress up old unexciting concrete causeways.
<b>SEALER</b>	<p><b>QUICKCRETE</b> must be sealed with either:</p> <p>QUICK SEAL (solvent base) – minimum 2 coats, OR CLEAR SEAL (acrylic base) – 3 coats if in high traffic areas.</p>
<b>SPECIFICATION</b>	<p>1<sup>st</sup> Coat: Apply Quickwall SKIMCOAT</p> <p>2<sup>nd</sup> Coat: Apply Quickwall PRIMER</p> <p>3<sup>rd</sup> Coat: Apply 1 coat of <b>QUICKCRETE</b></p> <p>4<sup>th</sup> Coat: Apply 1 coat of QUICK SEAL (Or Solvent based sealer)</p> <p>5<sup>th</sup> Coat: Apply 1 coat of QUICKSEAL</p> <p>Note: Clear Seal may be used instead of Quick Seal. (3 Coats)</p>