

STIPPLE TEX

TEXTURED CEILING FINISH

Acrylic



DESCRIPTION	STIPPLE TEX is best known for its crows foot stipple effect to beautify ceilings. It has the ability to hide off form concrete ceiling imperfections or joint lines and general impaired patches. STIPPLE TEX dries to a smooth rounded random stipple. Simply apply with a course yellow roller sleeve, or finish with a crows foot Stipple brush.
DISPENSING	10 litre & 20 litre packs.
COVERAGE	1 x 20 litre pail covers approx. 33m ² depending on the porosity of the substrate, equipment, rollers etc.
APPLICATION	<ul style="list-style-type: none"> • STIPPLE TEX can be applied with combs / sponges / brush strokes etc. to achieve designer ceilings. • Seal substrate with Quickwall SEALER and apply direct to the sealed substrate. • For uneven substrates or joints apply Quickwall SKIMCOAT, allow to dry and seal prior to the STIPPLE TEX application. • Seal with Quickwall SEALER.
SPECIAL FEATURES	<ul style="list-style-type: none"> • STIPPLE TEX is user friendly and maintains good wet edge properties. • Material is light weight and bonds to almost any substrate. • Contains excellent biocides to protect against fungi, bacteria and algae formation even in hot humid tropical environments. • May be applied with gravity hand held hopper guns or vermiculite spraying machines to provide the spray on splatter finishes from fine to medium and course builds.
PRE-STRESSED FLOORS	Excellent material to topcoat the underside of pre-stressed flooring systems.
APPROVED FOR	Government Projects, Defence Housing Authority, Commercial and Domestic applications.
GUARANTEE	Seven years when applied by an Approved Applicator and in accordance to Quickwall specification.
SPECIFICATION	<p>1st Coat: Apply Quickwall PRIMER</p> <p>2nd Coat: Apply Quickwall STIPPLE TEX</p> <p>3rd Coat: Apply 1 coat FLAT CEILING WHITE</p> <p>4th Coat: Apply 1 coat FLAT CEILING WHITE</p>