

JOINTING COMPOUND

NON-SOLVENT BASED

MULTI-USE JOINT FILLER



DESCRIPTION	QUICKWALL JOINTING COMPOUND is a tough universal water based filler compound ready to use straight from the pail for both external and internal applications to bridge joints on expanding and retracting substrates. It is a flexible co-polymer jointing compound.
SUITABLE FOR	QUICKWALL JOINTING COMPOUND will retain its elastomeric ability enabling it to be used in many applications such as: <ul style="list-style-type: none">• Flush out joints in pre cast concrete slabs pre-stressed flooring systems• Cement sheet abutments• Gap filler to off form concrete• Patch repair with alkali resistant fibreglass mesh to joints.• Expansion joint filler
SPECIAL FEATURES	<ul style="list-style-type: none">• Minimum shrinkage and can be worked thinly to a feather-edge without powdering or breaking down.• Has excellent keying ability.• Is compatible to all Quickwall construction products and virtually all substrate building materials.• Extremely resistant to all forms of fungicides or bacteria and application in tropical environs have not suffered after many years of extended use.• Environment and applicator friendly.
WASH UP / CARE	Wash up in water.
APPROVED FOR	Government Projects, Defence Housing Authority, Commercial and Domestic applications.
SPECIFICATION	<p>1st Step: Apply Quickwall PRIMER to substrate.</p> <p>2nd Step: Apply Quickwall JOINTING COMPOUND with appropriate tools.</p> <p>3rd Step: Place alkali resistant mesh into JOINTING COMPOUND where required.</p> <p>4th Step: Re-Apply one coat of JOINTING COMPOUND and flush outer joints to a feather edge.</p> <p>Note: Replace lid on container when not in use.</p>